

Challis Ag+ Safe Tap In Line Anti Bacterial Tap Filter 1509 Days 24/7 Protection



**Over 30,000 Ag+
showers already in
NHS Trusts Across the
UK**

Challis Ag+ Safe Tap In Line Micro Filtration for Anti Bacterial Protection for 150 Days 24/7

Product characteristics

- Hollow fiber membranes with micro-porous structure made of Polysulfone
- Dead-end Outside/In Filtration
- Extended membrane area for a high flow (good comfort of use) and a long life time minimum for 3,600 cm² (2.8 ft²) effective membrane area (**Over 3x as much as comparable filters currently available**)
- High thermal resistance of the vessel material
- Connection for standard shower hose

Main features

- Pore diameter 0.1µ
- Rejection > 99.99% for all bacteria
- Max pressure 5 bar (70 psi)
- Max Temperature 70°C
- Life Time 30,000 liters 150 Days(for standard E.U Average Drinking Water Quality) Instantaneous Protection

Applications

For bacteriologic protection on shower water :

- Emergency Use
- Home,
- Healthcare centers (hospital, nursing, dentist),
- Hostels,
- Fitness centers (swimming pool, spa),
- Recreational centers,
- Camping Centers, Cruise ships and Ferries ...

A water contamination with pathogens, even light, can constitute a real sanitary danger ,one famous example being Legionella. The most efficient solution is a filtration at the point of use. Challis Ag+ Safe Tap is a microfiltration membrane cartridge which retains high bacterial charges and thus avoids contamination and its consequences. It secures the water at the point of use and particularly the showers in high dependency areas where the risk is high.

Bacteria free water legionella prevention

The Challis Ag+ Safe Tap is composed of microfiltration hollow fiber membranes inserted in the tap filter. The membrane pore size of 0.1 micron, that is to say smaller than the smallest micro-organism, allows to obtain the optimal filtration and an increased protection. Legionella bacteria (0.5 - 0.7 micron in size) occurring naturally in surface water, frequently found in tap plumbing and re-sponsible of Legionellosis diseases are rejected. The Challis Ag+ Safe Tap microfilter membrane is manufactured to the highest of standards. These mem-branes are NSF61 and ACS (French Health Ministry) approved.

High flow and Long Working Life

Challis Ag+ Safe Tap offers the best technological solution to contamination prevention. The water passes from the outside to inside of the hollow fiber membrane (small porous plastic tubes less than one millimeter in diameter) barrier while the suspended matters and bac-teria are captured on the membrane surface. The hollow fiber membrane material (Polysulfone) and the outside/ in filtration water circulation offer a high chemical and mechanical durability, an extended filtration membrane area for high flow allowing a good comfort of use and high membrane surface for a long life time, significantly out performing many of the filters currently available.

Easy installation, instantaneous protection

The Challis Ag+ Safe Tap including membrane features universal fitting to simply screw it to any ordinary modern threaded tap. The bacteriological protection starts immediately after installation. Produced flow will decrease but bacteriologic protection is always kept



Product Code: M22 Fitting CWC418

Product Code: M24 Fitting CWC419

Technical Document	Technical Data Sheet		
Challis Water Controls Ag+	06/15	Challis Ag+ Tap MicroFilter	MicroFilter for Bacteriologic Filtration-Point of Use Tap

Challis Ag+ Tap MicroFilter		Characteristics
Hollow finer type		MFXS
Membrane Area	cm ²	3600
Threshold	µm	0.10
Fiber External Diameter	mm	0.45
Water Flow @ 3 Bar @20°C	L/mn	+12
Pressure Drop @ 2 L/min	bar	0.30
Operating Pressures	bar	3-4
Maximum Pressure	bar	5
Maximum Operating Temperature	°C	60
Maximum temperature pointed and 30 mn maximum during the lifetime Micrfilter	°C	70
Ph Range	pH	2-14
Life Time on Normalized Municipal	Days	150
Weight Without Water Inside	gr	120
Length	cm	10.3
Diameter	cm	4.7
Fitting		M24 or M22
Chlorine resistance test for 12 hours at 25ppm or 300ppm/h		

Challis Ag+ Tap Micro Filter	Materials & Agreements
Materials for vessel, deflector, tip & knob	ABS
Check Valve Materials	POM, Stainless Steel Silicon - NSF61
Hollow Fibre Material	Polysulfone ACS/French Ministry of Health & NSF61 Approval
Resin Material For potting	Polyurethane ACS/French Ministry of Health & NSF61 Approval



CHALLIS
ANTIBACTERIAL

